

	MODEL	Α	В	С	D	Е	F	G		
	MODEL	Jacket Diameter	Tank Diameter	Height to Hot Out	Height to Pan	Height to Thermistor	Cold In & Hot Out Fitting Size	Dip Tube Fitting Size		
	P30FC	22.75	18	40.5	37.75	21	3/4" NPT	3/4" NPT		
	P45FC	22.75	18	53.5	50.25	25	3/4" NPT	3/4" NPT	PT	
A	P55FC	28	24	41	38.125	21	3/4" NPT	3/4" NPT		
	P80FC	28	24	53.5	50.25	25	3/4" NPT	3/4" NPT		
	P120FC	28	24	74	69.5	35	3/4" NPT	3/4" NPT		

PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Variable Thorses of Core		
THE INFORMATION CONTAINED IN THIS	DIMENSIONS ARE IN INCHES TOLERANCES: LINEAR: 1 Decimal Place = ± 0.1 2 Decimal Place = ± 0.01 3 Decimal Place = ± 0.05 ANGULAR: 0 Decimal Place = ± 1.0° 1 Decimal Place = ± 0.5° INTERPRET GEOMETRIC TOLERANCING PER:	DRAWN	RP	11/13/2015	Vaughn Thermal Corp.		
DRAWING IS CONFIDENTIAL AND PROPRIETARY, THE CONTENTS OF THIS		CHECKED	RP	11/15/2023	Tank Assembly		
DRAWING ARE THE SOLE PROPERTY OF VAUGHN THERMAL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE		ENG APPR.					
WITHOUT THE WRITTEN PERMISSION OF VAUGHN THERMAL CORPORATION IS		MFG APPR.			Featherweight Storag		
PROHIBITED.		Q.A.			Configurations		
	MATERIAL:	COMMENTS:			SIZE DWG. NO. REV		
W VALIGHN					C V30A0005 K		
		D . DT					