



MODEL	A	B	C	D	E	F	G	H	I	J	K	L	M
	Jacket Diameter	Tank Diameter	Height to Pan	Height to T&P Relief Valve	Height to Immersion	Height to Top HX	Height to Bottom HX	Height to Cold In	Height to Drain	Height to T&P Relief Valve	Angle of Drain	Angle of Cold In	Angle of Immersion
65DHX62	26	22	46.125	39.375	28	20.875	10.875	8.375	7.875	45	45	55	55
80DHX62	26	22	57.125	49.875	28	20.875	10.875	8.375	7.875	45	45	55	55
80TDHX62	22.75	19	71.625	64.375	28	20.875	10.875	8.375	7.875	50	50	60	60
100DHX62	26	22	67.375	60.375	28	20.875	10.875	8.375	7.875	45	45	55	55
120DHX62	28	24	67.625	60.375	28	20.875	10.875	8.375	7.875	45	45	55	55

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY. THE CONTENTS OF THIS DRAWING ARE THE SOLE PROPERTY OF VAUGHN THERMAL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VAUGHN THERMAL CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES

TOLERANCES:

LINEAR: 1 Decimal Place = ± 0.1
2 Decimal Place = ± 0.01
3 Decimal Place = ± 0.005

ANGULAR: 0 Decimal Place = ± 1.0°
1 Decimal Place = ± 0.5°

INTERPRET GEOMETRIC TOLERANCING PER:

MATERIAL:

FINISH:

DRAWN	RP	6/24/2019
CHECKED	RP	4/28/2020
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		
PART NUMBER:		

NAME

DATE

6/24/2019

4/28/2020

Vaughn Thermal Corp.

TITLE:

Tank Assembly DHX62 Configurations

SIZE	DWG. NO.	REV
C	V41A0845	C
SCALE: 1:8	SHEETS: 1	