



MODEL	A	B	C	D	E	F	G
40SR	20	16	56.25	50	35.625	22.875	13.375
65SR	26	22	46.125	39.375	32.125	20.875	13.75
80SR	26	22	57.125	49.875	40.875	27.375	13.75
80TSR	22.75	19	71.375	64.375	49.875	36.125	13.75
100SR	26	22	67.375	60.375	47.875	34.125	13.75
120SR	28	24	67.625	60.375	47.875	34.125	17

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY. THE CONTENTS OF THIS DRAWING ARE THE SOLE PROPERTY OF VAUGHN THERMAL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VAUGHN THERMAL CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
LINEAR: 1 Decimal Place = ± 0.1
2 Decimal Place = ± 0.01
3 Decimal Place = ± 0.005
ANGULAR: 0 Decimal Place = ± 1.0°
1 Decimal Place = ± 0.5°
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL:
FINISH:

DRAWN: RP
CHECKED:
ENG APPR.:
MFG APPR.:
COMMENTS:
PART NUMBER:

NAME: RP
DATE: 6/24/2019

Vaughn Thermal Corp.
TITLE: Tank Assembly SR Configurations

SIZE: C
DWG. NO.: V41A0810
SCALE: 1:8

REV: A
SHEETS: 1