



MODEL	A	B	C	D	E
S30	20	16	40.625	34.25	25.75
S40	20	16	56.25	50	36.5
S50	22.75	19	49.75	42.875	32.125
S50T	20	16	66.5	60	47.5
S55	22.75	19	58.25	50.875	37.375
S65	26	22	46.25	39.375	32.125
S70	22.75	19	67.25	60.375	49.125
S80	26	22	57.25	49.875	40.625
S80T	22.75	19	71.75	64.375	47.875
S100	26	22	67.5	60.375	47.875
S120	28	24	67.75	60.375	47.875

*Single phase tanks are built with screw in elements

<small>PROPRIETARY AND CONFIDENTIAL</small> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VAUGHN THERMAL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VAUGHN THERMAL CORPORATION IS PROHIBITED.	<small>DIMENSIONS ARE IN INCHES</small> <small>TOLERANCES:</small> LINEAR: 0 Decimal Place = ± 0.1 1 Decimal Place = ± 0.01 2 Decimal Place = ± 0.005 ANGULAR: 0 Decimal Place = ± 1.0° 1 Decimal Place = ± 0.5° <small>INTERPRET GEOMETRIC TOLERANCING PER:</small>	<small>DRAWN</small> <small>CHECKED</small> <small>ENG APPR.</small> <small>MFG APPR.</small> <small>Q.A.</small> <small>COMMENTS:</small> <small>PART NUMBER:</small>	<small>NAME</small> RP <small>DATE</small> 10/21/2015	Vaughn Thermal Corp. TITLE: Tank Assembly Light Duty Commercial Series <small>SIZE DWG. NO.</small> C <small>SCALE: 1:12</small>
	<small>FINISH:</small>	<small>REV</small> A <small>SHEETS: 1</small>		